

MATERIAL SAFETY DATA SHEET

VALUE PRODUCTS, INC. 2128 INDUSTRIAL DRIVE, STOCKTON, CA 95206

PRODUCT CODE: 2095 DATE ISSUED : 03/16/06
REVISION : 3 DATE PREPARED: 06/29/00
SUPERSEDES : 08/10/95

SECTION I PRODUCT IDENTIFICATION

PRODUCT NAME : CONVEYOR LUBE
CHEMICAL NAME : WATER BASED DETERGENT SOLVENT BLEND
FORMULA : PROPRIETARY
DOT HAZARD CLASS : CORROSIVE, POTASSIUM HYDROXIDE SOLUTION, UN #1814

Table with 3 columns: HAZARD RATING (NFPA 704), HAZARD RATING, and PROTECTIVE EQUIPMENT. Rows include HEALTH: 3, FIRE: 0, REACTIVITY: 0, and PROTECTIVE EQUIPMENT: E.

CHEMTREC'S 24 HOUR EMERGENCY TELEPHONE NUMBER 800-424-9300

SECTION II HAZARDOUS INGREDIENTS

SUBSTANCES LISTED IN THIS SECTION ARE THOSE IDENTIFIED AS BEING PRESENT AT A CONCENTRATION OF 1% OR GREATER, OR 0.1% IF THE SUBSTANCE IS ON THE LIST OF POTENTIAL CARCINOGENS CITED IN OSHA HAZARD COMMUNICATION STANDARD.

Table with 4 columns: MATERIAL, CAS#, TLV, and PEL. Rows include POTASSIUM HYDROXIDE, ISOPROPYL ALCOHOL, and NTA (SODIUM NITRILOTRIACETATE).

NITRILOTRIACETIC ACID - CAS REG. NO. 139-13-9, IS LISTED AS CARCINOGEN UNDER NATIONAL TOXICOLOGY PROGRAM, AND IS IDENTIFIED AS A HAZARDOUS CHEMICAL UNDER THE CRITERIA OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) CALIFORNIA PROPOSITION 65 IDENTIFIES NTA AS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

SECTION III PHYSICAL DATA

BOILING POINT : 195 °F VOLATILE : >80%
VAPOR PRESSURE (AIR=1): >1 SOLUBILITY IN WATER: COMPLETE
VAPOR DENSITY (AIR=1): >1 SPECIFIC GRAVITY: 1.030
EVAPORATION RATE (WATER=1):>1 VISCOSITY: 550 CPS @68°F
PH OF CONCENTRATE SOLUTION: 13.0-14.0
DESCRIPTION: CLEAR, VISCOUS, AMBER SOLUTION, FATTY ODOR.

SECTION IV FIRE AND EXPLOSION HAZARDS

FLASH POINTS: NON-COMBUSTIBLE METHOD USED: C.O.C.
EXTINGUISHING MEDIA: WATER SPRAY, FOAM, CARBON DIOXIDE.
UNUSUAL FIRE OR EXPLOSIVE HAZARD: WATER RUN-OFF FROM FIRE FIGHTING MAY BE SLIPPERY. MAY GENERATE HYDROGEN GAS. REACT VIOLENTLY WITH METALS SUCH AS TIN, ZINC, ALUMINUM.

SECTION V HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF EXPOSURE (SKIN, EYE CONTACT; INHALATION; INGESTION)

EYE CONTACT : VAPORS, MISTS, OR LIQUID ARE CORROSIVE TO EYES. BRIEF DIRECT CONTACT TO EYES MAY CAUSE PAIN, LACHRYMATION (TEAR), AND SEVERE DAMAGE TO CORNEAL. SERIOUS INJURY MAY RESULT IN PERMANENT IMPAIRMENT OF VISION.
INHALATION : CORROSIVE TO NOSE, THROAT, AND MUCOUS MEMBRANE. EXCESSIVE EXPOSURE MAY CAUSE SEVERE INJURY TO UPPER RESPIRATORY TRACT AND LUNGS.

INGESTION : CAN CAUSE IRRITATION OR SEVERE BURN TO MOUTH, THROAT, AND GASTROINTESTINAL TRACT. MAY ALSO CAUSE ULCERATION. SWALLOWING LARGE QUANTITIES MAY CAUSE SERIOUS INJURY.

SKIN CONTACT : SHORT, SINGLE EXPOSURE MAY CAUSE SEVERE BURN TO SKINS.

FIRST AID MEASURES

EYE CONTACT : IMMEDIATELY FLUSH EYES WITH LOTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. HOLD EYELIDS APART TO ENSURE SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS.

INHALATION : REMOVE TO FRESH AREA. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESUSCITATION.

INGESTION : DO NOT INDUCE VOMITING. TREAT AS SOAP OR DETERGENT DIGESTION. DRINK LARGE QUANTITIES OF WATER AND SEEK MEDICAL ATTENTION IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONCIOUS PERSON.

SKIN CONTACT : WASH SKIN WITH LOTS OF WATER. IF IRRITATION OCCURS AND PERSISTS SEEK MEDICAL ATTENTION AS NEEDED.

SECTION VI REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG ACIDS, OXIDIZERS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: HIGH TEMPERATURE, SOURCES OF IGNITION.

HAZARDOUS DECOMPOSITION: FLAMMABLE HYDROGEN GAS, POISONOUS CARBON MONOXIDE.

SECTION VII SPILL OR LEAK PROCEDURES

CLEAN-UP PROCEDURES: CONTAIN SPILL WITH INERT MATERIAL THEN TRANSFER TO SEALABLE CONTAINERS FOR DISPOSAL. AVOID SPREADING. KEEP OUT OF PUBLIC BODY OF WATER, SEWERS, DRAINAGES. FLUSH CONTAMINATED AREAS WITH WATER AFTER ALL VISIBLE TRACES OF SPILLS HAVE BEEN REMOVED.

RECOMMENDED WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. NOTIFY APPLICABLE AUTHORITIES OF SPILLS AND DISPOSAL METHODS.

SECTION VIII SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION : GENERALLY NOT REQUIRED.

EYE PROTECTION : SAFETY GOGGLES.

PROTECTIVE CLOTHING : FULL-LENGTH CLOTHING.

VENTILATION : MECHANICAL VENTILATION

OTHER PROTECTIVE MEASURES: EYEWASH AND SAFETY SHOWER.

SECTION IX SPECIAL PRECAUTION

HYGIENIC PRACTICES IN HANDLING STORING: WASH THOROUGHLY AFTER HANDLING.

PRECAUTION TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL, DRY, VENTILATED AREAS. DO NOT OVERHEAT OR FREEZE. CONCENTRATED SOLUTION CAN BE SLIPPERY.

DISPOSAL OF EMPTY CONTAINER: EMPTY CONTAINERS SHOULD BE TRIPLE RINSED WITH WATER AND DISPOSED OF PURSUANT TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.

SECTION X USER'S RESPONSIBILITY

THE RESPONSIBILITY TO PROVIDE A SAFE WORKPLACE REMAINS WITH THE USER. THE USER SHOULD CONSIDER THE HEALTH HAZARD AND SAFETY INFORMATION CONTAINED HEREIN AS A GUIDE AND SHOULD TAKE THOSE PRECAUTIONS REQUIRED IN AN INDIVIDUAL OPERATION TO INSTRUCT EMPLOYEES AND DEVELOP WORK PRACTICE PROCEDURES FOR A SAFE WORK ENVIRONMENT.

THE INFORMATION CONTAINED HEREIN, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, IS ACCURATE. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

06/01/94 REVISED EMERGENCY PHONE NUMBER, HAZARD RATING SCALE
06/29/00 GENERAL REVISIONS