

MATERIAL SAFETY DATA SHEET

VALUE PRODUCTS INC 2128 INDUSTRIAL DRIVE STOCKTON CA 95206

PRODUCT CODE: 2220 REVISION : 3
DATE ISSUED: 10/27/07 SUPERSEDES : 12/17/05

SECTION I PRODUCT IDENTIFICATION

PRODUCT NAME: GREASE REMOVER
CHEMICAL NAME: SOLVENT SURFACTANT BLEND
FORMULA: PROPRIETARY
DOT HAZARD CLASS: NONE
HAZARD RATING (NFPA 704) HAZARD RATING PROTECTIVE EQUIPMENT
HEALTH: 2 0=MINIMAL A=GOGGLES
FIRE: 0 1=SLIGHT B=GOGGLES, GLOVES
REACTIVITY: 0 2=MODERATE C=GOGGLES, GLOVES, APRON
PROTECTIVE EQUIPMENT: B 3=SERIOUS D=GOGGLES, GLOVES, APRON, FACE SHIELD
4=SEVERE E=GOGGLES, GLOVES, RESPIRATOR
CHEMTREC'S 24 HOUR EMERGENCY TELEPHONE NUMBER 800-424-9300

SECTION II HAZARDOUS INGREDIENTS

SUBSTANCES LISTED IN THIS SECTION ARE THOSE IDENTIFIED AS BEING PRESENT AT A CONCENTRATION OF 1% OR GREATER, OR 0.1% IF THE SUBSTANCE IS ON THE LIST OF POTENTIAL CARCINOGENS CITED IN OSHA HAZARD COMMUNICATION STANDARD.

MATERIAL	CAS#	TLV	PEL
ETHYLENE GLYCOL MONO-BUTYL ETHER	000111-76-2	25 PPM	50 PPM

SECTION III PHYSICAL DATA

BOILING POINT: 212 °F VOLATILE: 84%
P_H (CONCENTRATE): 11.3 SOLUBILITY IN WATER: COMPLETE
VAPOR DENSITY: (AIR=1):>1 SPECIFIC GRAVITY: 1.050
EVAPORATION RATE (WATER=1):>1 VISCOSITY: 25 CPS @ 68 °F
DESCRIPTION: CLEAR ORANGE SOLUTION, BUTYL ODOR

SECTION IV FIRE AND EXPLOSION HAZARDS

FLASH POINTS: NON-COMBUSTIBLE METHOD USED: C.O.C.
EXTINGUISHING MEDIA: WATER SPRAY, FOAM, CO2, DRY CHEMICAL. WHEN USING WATER, FIRE RUN-OFF WATER MAY BE CORROSIVE.
UNUSUAL FIRE OR EXPLOSIVE HAZARD: MAY GENERATE HYDROGEN GAS. REACT MODERATELY WITH METALS SUCH AS TIN, ZINC, ALUMINUM.

SECTION V HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF EXPOSURE (SKIN, EYE CONTACT; INHALATION; INGESTION)

EYE CONTACT: VAPORS, MISTS, OR LIQUID ARE MODERATELY CORROSIVE TO EYES. BRIEF DIRECT CONTACT TO EYES MAY CAUSE PAIN, LACHRYMATION (TEAR).
INHALATION: IRRITATION TO NOSE, THROAT, AND MUCOUS MEMBRANE. EXCESSIVE EXPOSURE MAY CAUSE INJURY TO UPPER RESPIRATORY TRACT AND LUNGS.
INGESTION: CAN CAUSE IRRITATION OR BURN TO MOUTH, THROAT, AND GASTROINTESTINAL TRACT. MAY ALSO CAUSE ULCERATION. SWALLOWING LARGE QUANTITIES MAY CAUSE SERIOUS INJURY.
SKIN CONTACT: EXPOSURE MAY CAUSE IRRITATION OR BURN TO SKINS.

FIRST AID MEASURES

EYE CONTACT: IMMEDIATELY AND IMPERATIVELY FLUSH EYES WITH LOTS OF RUNNING WATER FOR AT LEAST 15 MINUTES, LIFTING THE UPPER AND LOWEREYELIDS TO ENSURE FLUSHING OF THE ENTIRE SURFACE. PROMPT MEDICAL ATTENTION IS ESSENTIAL.
INHALATION: REMOVE TO FRESH AREA. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. CALL A PHYSICIAN IMMEDIATELY.
INGESTION: DO NOT INDUCE VOMITING. DRINK LARGE QUANTITIES OF WATER AND TRANSPORT VICTIM TO MEDICAL FACILITY IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SKIN CONTACT: WASH SKIN WITH LOTS OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND SHOES; WASH BEFORE REUSE. IF IRRITATION OCCURS AND PERSISTS SEEK MEDICAL ATTENTION.

SECTION VI REACTIVITY DATA

STABILITY: STABLE
 INCOMPATIBILITY (MATERIALS TO AVOID): STRONG ACIDS OR OXIDIZERS.
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
 CONDITIONS TO AVOID: DIRECT FLAME.
 HAZARDOUS DECOMPOSITION: FLAMMABLE HYDROGEN GAS UPON CONTACT WITH METALS.

SECTION VII SPILL OR LEAK PROCEDURES

CLEAN-UP PROCEDURES: ONLY TRAINED AND PROPERLY PROTECTED PERSONNEL SHOULD BE INVOLVED IN SPILLED CLEAN-UP OPERATIONS. WEAR PROTECTIVE CLOTHING. MOP UP AND PLACE MATERIAL IN SEALABLE CONTAINERS FOR DISPOSAL. KEEP OUT OF SEWER SYSTEM, SURFACE WATER. FLUSH CONTAMINATED AREAS WITH WATER AFTER ALL TRACES OF VISIBLE SPILLS HAVE COMPLETELY RECOVERED.
 RECOMMENDED WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. ENSURE THAT ALL APPLICABLE AGENCIES RECEIVE PROPER NOTIFICATION OF SPILL AND DISPOSAL METHODS.

SECTION VIII SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: NIOSH-APPROVED RESPIRATOR IN OVER-EXPOSURE CONDITION.
 EYE PROTECTION: CHEMICAL GOGGLES.
 PROTECTIVE CLOTHING: RUBBER GLOVES, APRON. FULL-LENGTH CLOTHING.
 VENTILATION: EYEWASH AND SAFETY SHOWER.

SECTION IX SPECIAL PRECAUTION

HYGIENIC PRACTICES IN HANDLING STORING: WASH THOROUGHLY AFTER HANDLING.
 PRECAUTION TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL, DRY, VENTILATED AREAS.
 DISPOSAL OF EMPTY CONTAINER: EMPTY CONTAINERS SHOULD BE TRIPLE RINSED WITH WATER AND DISPOSED OF PURSUANT TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.

SECTION X USER'S RESPONSIBILITY

THE **RESPONSIBILITY** TO PROVIDE A SAFE WORKPLACE REMAINS WITH THE USER. THE USER SHOULD CONSIDER THE HEALTH HAZARD AND SAFETY INFORMATION CONTAINED HEREIN AS A GUIDE AND SHOULD TAKE THOSE PRECAUTIONS REQUIRED IN AN INDIVIDUAL OPERATION TO INSTRUCT EMPLOYEES AND DEVELOP WORK PRACTICE PROCEDURES FOR A SAFE WORK ENVIRONMENT.

THE INFORMATION CONTAINED HEREIN, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, IS ACCURATE. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.
