

PRIDE  **LINE**

QUICK STRIP

HEAVY-DUTY STRIPPER FOR HARD ACRYLIC FLOOR FINISHES

DESCRIPTION:

QUICK STRIP chemically qualifies tough acrylic cross-link floor finishes for easy pick up with minimum scrubbing. It cleans and strips in one step, saving time and labor. It takes the long hours and backache out of floor stripping. Simply mix, spray-on, scrub and vacuum off. It is your best attack against tough, metallic interlock finish buildup.

QUICK STRIP can be diluted with up to 8 parts of water for added economy. It will not soften asphalt or vinyl tiles like some other strippers. It strips rubber, vinyl, vinyl asbestos, ceramic and quarry tile, marble, terrazzo and concrete. It's biodegradable, too.

COLOR: Clear Liquid

DIRECTIONS:

EQUIPMENT: Dust mop or push broom, towels, black stripping pads, single brush floor machine, three mop buckets and wringers, three synthetic mops and handles, abrasive pad or brush and handle, QUICK STRIP measuring cup and wet vacuum. If you have a large building consider investing in an Auto-scrubber. This will significantly cut labor cost.

PROCEDURE:

Step 1: Sweep away all loose dirt and trash.

Step 2: Place towels in all doorways and entryways.

Step 3: Place a black strip pad under a single brush floor machine and dry hone heavy buildup along edges and baseboards.

Step 4: Mix QUICK STRIP solution with hot water (120°F to 140°F) for best results as follows:

Heavy Build-up: Dilute 1 to 1 with hot water.

Medium Build-up: Dilute 1 to 4 with hot water.

Light Build-up: Dilute 1 to 8 with hot water.

Step 5: Apply a liberal amount of QUICK STRIP to an area approximately 10 feet by 20 feet. Allow 5 minutes dwell time or until the finish is liquefied. **IMPORTANT:** Do not let the stripper dry on the floor.

Step 6: Place a black strip pad in a bucket of stripping solution to soak. Slowly rotate the pad until it's saturated.

Step 7: Place saturated black strip pad under the single brush floor machine and scrub the floor in a back and forth motion. Scrub in both directions to make sure all the old coating is removed.

Step 8: to remove buildup and dirt along baseboards, use an abrasive pad or brush (Doodlebug).

Step 9: After each section has been scrubber in both directions, pick up with wet a vacuum.

Step 10: Thoroughly rinse the section you just scrubbed with clear water.

Step 11: Damp mop the floor twice with a bucketful of clean water with 1 cup of vinegar and let dry.

Step 12: Inspect the floor to be sure all the old coatings and stripping solution has been removed. A good test is to wipe your hand across the floor. If your hand is clean, so is your floor.

IMPORTANT: Change the rinse water frequently to insure all residue is removed. Stripper residue left on the floor from improper rinsing will keep your polish or wax from bonding properly.

PRODUCT FEATURES / CUSTOMER BENEFITS

- Concentrated / Economical use costs
- Caustic Detergent / See MSDS for instructions

No.	Size	Qty./Unit
• 2422	1 Gal.	4 Case
	5 Gal.	1 Pail

Safety Reminder

Before using this or other products, make sure your employees read and understand the product label and the Material Safety Data Sheet.